

2207-60

Wireless IP CowCam with 1080p, 5km Range Distance with WIFI Bridge.



Key Vaule Highlight

- Smart phone Accessing

The user can watch the live thru smart phone via app.

- Color view at night

Built-in visible light can deliver color video at night.

- HD Image Detail

The 2207-60 Camera can provide image detailed in 1080p Full HD with its 1/2.8 inch CMOS sensor.

- Wireless setup.

The 2207-60 camera can works with WIFI bridge (NOT included) to build the wireless connectino up to 5km

- Waterproof

The users can deploy the 2207-60 camera in the harsh environment outside.

Typical Application

Livestock cow watching

Specification

Power	
Input voltage	+12 VDC or Power-over-Ethernet
Power consumption	6 W (max)
Video	
Sensor type	1/2.8 Type CMOS Sensor
Sensor pixels	1920x1080
Sensitivity	0.5 lx (IR off) 0 lx (IR on)
Main-stream Resolution	1920*1080@25fps, 1280*720@25fps
Sub-stream Resolution	4CIF@25fps; CIF@25fps
Video compression	H.264 MP (Main Profile)
DWDR	On/Off
3D DNR	Yes
Night vision	
Distance	30 m
LED	6 LED high efficiency array, 650 nm
Lens	
Lens type	3.6 mm MP lens, Fixed Iris F1.4
Field of View	H: 75°
Lens mount	Board mounted
Day & Night	On/Off
Connection (optional)	
Alarm input	1 alarm in
Alarm out	1 alarm out
Audio (optional)	
Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)
Local Storage (optional)	
Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 10 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule recording

Software Control	
Unit configuration	Via web browser or PC surveillance software
Network	
Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
Wireless	N/A
PoE (optional)	IEEE 802.3af compliant
Mechanical	
Dimensions	TBA
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
Color View LiveStock IP Camera	2207-60