

2252-23

Remote Zoom 2MP Heavy-duty Camera



Key Vaule Highlight

- High definition image detail

Users can zoom in the 2252-23 camera remotely to get the best view of the interested area. Allocate all 2 megapixel to a specific area can make the image extremely clear.

- Moving object capturing

2252-23 camera is capable of capturing moving objects and deliver less blurry image which is value for POS area, entrance or exit.

- Night vision

The 2252-23 camera can capture clear image at night with its built-in infrared LEDs.

- Simple setup.

Users only need single cable to carry the power and network to the camera. The power will be separated from the network cable with POE function.

- Efficient recording

Users can enable the motion detection to trigger footage recording when people walk in. They only need to review the motion footage to locate the person of interests. Pre-record capability makes sure the detail will not be missing.

Typical Application

Headquarter office

Hotel

Logistics Center

Retail

convenience store

and others

Specification

Power

Input voltage	+12 VDC or Power-over-Ethernet
Power consumption	6 W (max)

Video

Sensor type	1/2.8 Type SONY Exmor CMOS Sensor
Sensor pixels	1920x1080
Sensitivity	0.1 lx (IR off) 0 lx (IR on)
Main-stream Resolution	1920x1080@25fps; 1280x720@25fps
Sub-stream Resolution	4CIF@25fps; CIF@25fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes

Night vision

Distance	30 m
LED	30 LED high efficiency array, 850 nm

Lens

Lens type	Motorized 2.8 to 12 mm, Fixed Iris F1.4
Field of View	H: 85° - 26°
Lens mount	Board mounted
Day & Night	Auto ICR Switch (IR correction filter)

Connection

Alarm input (optional)	1 alarm in
Alarm out (optional)	1 alarm out

Audio (optional)

Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)

Local Storage (optional)

Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 10 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule recording

Software Control

Unit configuration	Via web browser or PC surveillance software
--------------------	---

Network

Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
Wireless	N/A
PoE	IEEE 802.3af compliant

Mechanical

Dimensions	Diameter: 130 mm Height: 105 mm
Weight	TBA

Environmental

Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)

Ordering Information

IR IP Dome MF 2.8~12mm lens	2252-23
--------------------------------	---------

* Local Storage function is optional