

2369-30

Remote Focus 2MP IP Camera



Key Vaule Highlight

- High definition image detail

Users can zoom in the 2369-30 camera remotely to get the best view of the interested area. Allocate all 2 megapixel to a specific area can make the image extremely clear.

- Moving object capturing

2369-30 camera is capable of capturing moving objects and deliver less blurry image which is value for entrance or exit.

- Color night-vision Image

The 2369-30 camera can deliver color night-vision image with extra detail in the low light condition.

- Deterrence

The heavy duty design can create deterrence for the criminal which has different agenda. The cable management bracket eliminate the vandal issue of the camera.

- Waterproof

The users can deploy the 2369-30 camera in the harsh environment outside perimeter with heavy wind, rain, and snow.

- Simple and professional setup.

The users can easily test the camera on the field with its hang-up conjunction box. POE function allows single cable to carry the power and network to the camera. The power will be separated from the network cable.

Typical Application

Headquarter office

Hotel

Logistics Center

Retail

convenience store

and others

Specification

Power	
Input voltage	+12 VDC or Power-over-Ethernet
Power consumption	6 W (max)
Video	
Sensor type	1/2.8 Type SONY Exmor CMOS Sensor
Sensor pixels	1920x1080
Sensitivity	0.01 lx (IR off) 0 lx (IR on)
Main-stream Resolution	1920x1080@25fps; 1280x720@25fps
Sub-stream Resolution	4CIF@25fps; CIF@25fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes
Night vision	
Distance	50 m
LED	4 unit high power IR array, 850 nm
Lens	
Lens type	Motorized 2.8 to 12 mm, Fixed Iris F1.4
Field of View	H: 85°- 26°
Lens mount	Board mounted
Day & Night	Auto ICR Switch (IR correction filter)
Connection	
Alarm input (optional)	1 alarm in
Alarm out (optional)	N/A
Audio (optional)	
Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)

Software Control	
Unit configuration	Via web browser or PC surveillance software
Network	
Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
Wireless	N/A
PoE	IEEE 802.3af compliant
Mechanical	
Dimensions	Diameter: 150 mm Height: 130mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
IR IP Bullet MF 2.8~12mm lens	2369-30