

2654-83

AHD Mini Pinhole Camera



Key Vaule Highlight

- Covert design

The users can have advances for their investigation by setting up a 2654-83 AHD Mini Pinhole Camera.

- HD Image Detail

The 2654-83 AHD Mini Pinhole Camera can provide image detailed in 2MP HD resolution with its 1/3 inch CMOS sensor.

- Re-use the coaxial cable.

The user can re-use existed coaxial cable to upgrade the analog system to HD CCTV with 2654-83 AHD Mini Pinhole Camera.

Typical Application

Retail

Convenience Store

Workshop

Logistics center

and others

Specification

Power	
Input voltage	+12 VDC
Power consumption	4.5 W (max)
Video	
Sensor type	1/3 Type CMOS Sensor
Sensor pixels	1920*1080
Sensitivity	1.0 lx (IR off)
Resolution	1920*1080
Video Output	1 composite video 1 Vpp 75 ohm automatic termination
Day & Night	Auto
Shutter	Auto (1/50(1/60)s to 1/10,000s)
AGC	Auto
Night vision	
LED	N/A
Lens	
Lens type	3.7mm
Field of View	H: 67°
Lens mount	Board mounted
Day & Night	N/A
Mechanical	
Dimensions	37*37*20mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
AHD Mini pinhole Camera	2654-83

Guangzhou

No.3 East Alley, Guangfeng East Road,
Zengchen District, Guangzhou., 511300,
P.R.China
Tel: +86-20-8244-2660
Fax: +86-20-8274-5925
Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,
Baoan District, Shenzhen, 518000,
P.R.China
Tel: +86-755-81465995
Fax: +86-755-81469770
Email: sales@golbong.com