

## 2670-56

# WIFI PT Indoor Camera



### Key Vaule Highlight

**- Pan/tilt Coverage.**

Users can pan and tilt 2670-56 camera remotely to monitor the whole area with no blind spot.

**- Two way audio**

The user can communicate with their family with built-in G-voice engine.

**- Easy of use**

The user can easliy access the camera remotely with cloudID.

**- Night vision**

The 2670-56 camera can capture clear image at night with its built-in infrared LEDs.

**- Simple setup.**

Users can connect the 2670-56 camera to the network with WIFI. It eliminates the requirement to wire back to a router.

### Typical Application

Home

Retail

Convenience Store

Workshop

Office

and others

## Specification

Power	
Input voltage	+12 VDC
Power consumption	8.0 W (max)
Video	
Sensor type	1/3 inch Type CMOS Sensor
Sensor pixels	1280x960
Sensitivity	0.8 lx (IR off) 0 lx (IR on)
Main-stream Resolution	1280x960@18fps;1280x720@25fps
Sub-stream Resolution	4CIF@15fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes
Night vision	
Distance	10 m
LED	12 LED high efficiency array, 850 nm
Lens	
Lens type	3.6 mm pinhole lens
Field of View	H: 76°
Lens mount	Board mounted
Day & Night	Auto
Audio	
Audio input	Built-in mic
Audio output	Built-in speaker
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)
Local Storage	
Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 8 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule recording

Software Control	
Unit configuration	Mobile app
Network	
Protocols	HTTP, TCP/IP, RTSP, RTP, UDP, SMTP, DHCP, DNS, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
Wireless	IEEE 802.11b/g/n
PoE	N/A
Mechanical	
Dimensions	105*80.5mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
WIFI PT Indoor Camera	2670-56