

2671-52

WIFI Window Camera



Key Vaule Highlight

- High definition image detail

Users can deploy the 2671-52 windows camera monitor outside from indoor. Manual zoom allows user to get the best view of the interested area.

- All-in-one camera system

Users can choose either deploying camera standalone or add the camera to the existed surveillance system. The footage can be recorded in the TF card inside the camera. Users don't need to take off memory card to retrieve the footage, They can access the camera remotely over the network connection.

- Efficient recording

Users can enable the motion detection to trigger footage recording when people walk in. They only need to review the motion footage to locate the person of interests. Pre-record capability makes sure the detail will not be missing.

- Simple setup.

Users can connect the 2671-52 camera to the network with WIFI. It eliminates the requirement to wire back to a router.

Typical Application

Home

Retail

Convenience Store

Workshop

Office

and others

Specification

| Power | |
|------------------------|--|
| Input voltage | +12 VDC |
| Power consumption | 6.0 W (max) |
| Video | |
| Sensor type | 1/3 inch Type CMOS Sensor |
| Sensor pixels | 1280*960 |
| Sensitivity | 0.5 lx (IR off) 0 lx (IR on) |
| Main-stream Resolution | 1280x720@22fps |
| Sub-stream Resolution | 4CIF@25fps |
| Video compression | H.264 MP (Main Profile) |
| DWDR | ON/OFF |
| 3D DNR | Yes |
| Lens | |
| Lens type | 2.8-12mm manual zoom |
| Field of View | H: 85°-30° |
| Lens mount | Board mounted |
| Day & Night | IR cut filter |
| Connection | |
| Analog video out | N/A |
| Alarm input (optional) | 1 alarm in |
| Alarm out (optional) | N/A |
| Audio (optional) | |
| Audio input | RCA jack connector |
| Audio output | RCA jack connector |
| Audio communication | Two-way, full duplex |
| Audio compression | G.711 (live and recording) |
| Local Storage | |
| Memory card slot | Supports up to 128 GB micro SD card (An SD card of Class 8 or higher is recommended for HD recording) |
| Recording | Continuous recording, Motion/schedule recording |

| Software Control | |
|------------------------------|---|
| Unit configuration | Via web browser or PC surveillance software |
| Network | |
| Protocols | HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x |
| Ethernet | N/A |
| Wireless | IEEE 802.11b/g/n |
| PoE | N/A |
| Mechanical | |
| Dimensions | 105*80.5mm |
| Weight | TBA |
| Environmental | |
| Operating temperature Camera | -20 °C to +55 °C (-4 °F to +131 °F) |
| Storage temperature | -20 °C to +70 °C (-4 °F to +158 °F) |
| Humidity | 10% to 80% relative humidity (non condensing) |
| Ordering Information | |
| WIFI window Camera | 2671-52 |