

## 2673-32

### Micro Bullet HD Camera



#### Key Vaule Highlight

**- Covert Design**

The discreet design make the camera easy to blend into business environment. The customer will more feel comfortable without seeing the camera shooting on them.

**- HD Image Detail**

The 2673-32 Micro Bullet HD Camera can provide image detailed in 2MP HD resolution with its 1/2.8 inch CMOS sensor.

**- Plug & play Setup**

The user can plug 2673-32 Micro Bullet HD Camera to GOLBONG AHD DVR, no need to configure each of the camera front-end.

#### Typical Application

Retail

Convenience Store

Workshop

Logistics center

and others

## Specification

### Power

Input voltage	+12 VDC
Power consumption	4.5 W (max)

### Video

Sensor type	1/2.8 Type SONY Exmor CMOS Sensor
Sensor pixels	1920x1080
Sensitivity	0.5 lx (IR off)
Resolution	1920x1080
Video Output	1 composite video 1 Vpp 75 ohm automatic termination
Day & Night	Auto
Shutter	Auto (1/50(1/60)s to 1/10,000s)
AGC	Auto

### Night vision

LED	N/A
-----	-----

### Lens

Lens type	2.8 mm, Fixed Iris F1.4
Field of View	H: 92°
Lens mount	Board mounted
Day & Night	Auto

### Mechanical

Dimensions	Diameter:20.5 mm Lenght: 65 mm
Weight	TBA

### Environmental

Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)

### Ordering Information

1080p Micro Bullet HD Camera	2673-32
------------------------------	---------