

2673-52

Micro Bullet HD Camera



Key Vaule Highlight

- Covert Design

The discreet design make the camera easy to blend into business environment. The customer will more feel comfortable without seeing the camera shooting on them.

- HD Image Detail

The 2673-52 Micro Bullet HD Camera can provide image detailed in 2MP HD resolution with its 1/2.8 inch CMOS sensor.

- Ultra Wide Angle View

Users can deploy 2673-52 Camera to cover wide area with activities monitoring.

- Plug & play Setup

The user can plug 2673-52 Micro Bullet HD Camera to GOLBONG AHD DVR, no need to configure each of the camera front-end.

Typical Application

Retail

Convenience Store

Workshop

Logistics center

and others

Specification

| Power | |
|------------------------------|--|
| Input voltage | +12 VDC |
| Power consumption | 4.5 W (max) |
| Video | |
| Sensor type | 1/2.8 Type SONY Exmor CMOS Sensor |
| Sensor pixels | 1920x1080 |
| Sensitivity | 0.5 lx (IR off) |
| Resolution | 1920x1080 |
| Video Output | 1 composite video 1 Vpp 75 ohm automatic termination |
| Day & Night | Auto |
| Shutter | Auto (1/50(1/60)s to 1/10,000s) |
| AGC | Auto |
| Night vision | |
| LED | N/A |
| Lens | |
| Lens type | 2.1 mm, Fixed Iris F1.4 |
| Field of View | H: 135° |
| Lens mount | Board mounted |
| Day & Night | Auto |
| Mechanical | |
| Dimensions | Diameter:20.5 mm Lenght: 65 mm |
| Weight | TBA |
| Environmental | |
| Operating temperature Camera | -20 °C to +55 °C (-4 °F to +131 °F) |
| Storage temperature | -20 °C to +70 °C (-4 °F to +158 °F) |
| Humidity | 10% to 80% relative humidity (non condensing) |
| Ordering Information | |
| 1080p Micro Bullet HD Camera | 2673-52 |