

## 2676-21

# 4MP 2-Sensor Camera Station



### Key Vaule Highlight

#### - Flexible Coverage

Users can adjust the shooting direction of each sensor, even change the lens to achieve the optimal viewing angle.

#### - Watching Corridor

Users can deploy 2676-21 camera to monitor the same direction but different distance such as corridor.

#### - 180 Panoramic View

User can put two sensors together to have 180 degree panoramic view.

#### - Moving object capturing

2676-21 camera is capable of capturing moving objects and deliver less blurry image which is value for POS area, entrance or exit.

#### - Saving installation cost

The users can wire single cable and install 2 camera at once. POE function allows one cable to carry the power and network to the camera.

#### - Working with Regular NVR

The 2676-21 camera can work with regular standalone NVR for footage recording.

#### - Complete Open

The users can deploy 2676-21 camera with 3rd-party software basing Onvif protocols.

### Typical Application

Convenience Store

Headquarter office

Workshop

Logistics

Retail

and others

## Specification

Power	
Input voltage	+12 VDC or Power-over-Ethernet
Power consumption	15 W (max)
Video	
Sensor type	1/2.8 Type SONY Exmor CMOS Sensor
Sensor pixels	1920x1080
Sensitivity	0.1 lx (IR off)
Main-stream Resolution	2 stream 1920x1080@25fps
Sub-stream Resolution	2 stream 4CIF@25fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes
Night vision	
LED	N/A
Lens	
Lens type	3.6 mm, Fixed Iris F1.4
Field of View	75 degree x 2
Lens mount	Board mounted
Day & Night	Auto ICR Switch
Connection	
Analog video out	N/A
Alarm input (optional)	1 alarm in
Alarm out (optional)	N/A
Audio (optional)	
Audio input	RCA jack connector
Audio output	RCA jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)

Software Control	
Unit configuration	Via web browser or PC surveillance software
Network	
Protocols	HTTP, TCP/IP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPNP, NTP, 802.1x
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
IP address	2 independent IP address
Wireless	N/A
PoE	IEEE 802.3at compliant
Mechanical	
Dimensions	Diameter: 122 mm Height: 148 mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
4MP 2-Sensor Camera Station	2676-21