

4082-51

HD Mini Dome Vehicle Camera



Key Vaule Highlight

- HD Image Detail

The 4082-51 camera can deliver image detailed in 720p HD resolution with its 1/3 inch sensor.

- Compact design

The compact design can improve the customers experience in the vehicle.

- Anti-vibration Design

The 4082-51 camera can stand the vibration in the vehicle.

- Ultra Wide Angle View

Users can deploy 4082-51 camera to cover 102 degree wide area in front or rear of the vehicle.

- Night vision

The 4082-51 camera can capture clear image at night with its built-in infrared LEDs.

Typical Application

School bus

Truck

Logistics

Van

other Vehicle

Specification

Power	
Input voltage	+12 VDC
Power consumption	6 W (max)
Video	
Sensor type	1/3 inch Type Low lux CMOS Sensor
Sensor pixels	1280x720
Sensitivity	0.1 lx (IR off) 0 lx (IR on)
Resolution	1280x960
Video Output	1Vp-p Composite Output(75Ω/BNC)
Day & Night	photocells control
Shutter	Auto (1/50(1/60)s to 1/10,000s)
AGC	Auto
Night vision	
Distance	<5 m
LED	15 LED high efficiency array, 850 nm
Lens	
Lens type	2.8mm
Field of View	H: 102°
Lens mount	Board mounted
Day & Night	Auto ICR Switch
Mechanical	
Dimensions	Diameter:100 mm Lenght: 75 mm
Weight	TBA
Environmental	
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Ordering Information	
720p Coaxial Analog HD Vehicle Camera	4082-51

Guangzhou

No.3 East Alley, Guangfeng East Road,
Zengchen District, Guangzhou., 511300,
P.R.China
Tel: +86-20-8244-2660
Fax: +86-20-8274-5925
Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,
Baoan District, Shenzhen, 518000,
P.R.China
Tel: +86-755-81465995
Fax: +86-755-81469770
Email:sales@golbong.com