## 4201-56

# Panorama 180 Indoor Camera



### **Key Vaule Highlight**

#### - Discreet design

The discreet design make 4201-56 camera easy to blend into your home environment.

#### - Multiple Pupose

User can re-deploy the camera easily to monitor the home during the vacation.

#### - Two way audio

The parent can talk to their children and make the communication with built-in G-voice engine.

#### - Easy of use

The user can easily access the camera remotely with cloudID.

#### - Night vision

The 4201-56 camera can capture clear image at night with its built-in infrared LEDs.

#### - Simple setup.

User can connect the 4201-56 camera to the network with WIFI. It eliminates the requirement to wire back to a router.

#### **Typical Application**

Home

Retail

Convenience Store

Workshop

Office

and others

# **GOLBONG**

## **Specification**

Power	
Input voltage	+12 VDC
Power consumption	4.5 W (max)
Video	
Sensor type	1/4 inch Type CMOS Sensor
Sensor pixels	1280x720
Sensitivity	1.0 lx (IR off) 0 lx (IR on)
Main-stream Resolution	1280x720@25fps
Sub-steam Resolution	4CIF@15fps
Video compression	H.264 MP (Main Profile)
DWDR	ON/OFF
3D DNR	Yes
Night vision	
Distance	10 m
LED	12 LED high efficiency array, 940 nm
Lens	
Lens type	1.1 mm pinholel lens
Field of View	H: 180°
Lens mount	Board mounted
Day & Night	Auto
Audio	
Audio input	Built-in mic
Audio output	Built-in speaker
Audio communication	Two-way, full duplex
Audio compression	G.711 (live and recording)
Local Storage	
Memory card slot	Supports up to 128 GB micro SD card (An SD card of Class 8 or higher is recommended for HD recording)
Recording	Continuous recording, Motion/schedule

Software Control		
Unit configuration	Mobile app	
Network		
Protocols	HTTP, TCP/IP,RTSP, RTP, UDP, SMTP, DHCP, DNS, NTP, 802.1x	
Ethernet	N/A	
Wireless	IEEE 802.11b/g/n	
PoE	N/A	
Mechanical		
Dimensions	105*80.5mm	
Weight	ТВА	
Environmental		
Operating temperature Camera	-20 °C to +55 °C (-4 °F to +131 °F)	
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)	
Humidity	10% to 80% relative humidity (non condensing)	
Ordering Information		
WIFI PT Indoor Camera	4201-56	



#### Guangzhou

No.3 East Alley, Guangfeng East Road, Zengchen District, Guangzhou., 511300, P.R.China Tel: +86-20-8244-2660 Fax: +86-20-8274-5925 Email: sales@golbong.com

#### Shenzhen

1/F Block 295, Jiuwei, Xixiang Town, Baoan District, Shenzhen, 518000, P.R.China Tel: +86-755-81465995 Fax: +86-755-81469770 Email::sales@golbong.com