

# 4920-19

## 2K 4CH H.265 PoE System Kit



### Key Feature Highlight

#### - HD Image Detail

The 4920-19 system can deliver image detailed in 4MP ultra HD resolution with its 1/3 inch CMOS sensor.

#### - Complete setup in minutes, not an hour

The users can setup the IP system with quick set module which will assign the IP address and make the connection to each camera automatically.

#### - Built in PoE switch

The PoE NVR can send the network and power to each camera with single cable. No need extra power source at camera end.

#### - H.265 Next Level Codec

The 4920-19 system can deliver 30% ~ 50% extra recording capability with its H.265 codec.

#### - Motion recording and playback

The 4920-19 system can start record the video stream when the motion is detected by the camera. The operator doesn't need to playback all the footage, but only interests section.

#### - Discreet design

The discreet design make the camera easy to blend into business environment.

#### - Night vision

The IP camera can capture clear image at night with its built-in infrared LEDs.

### Typical Application

Retail

Convenience Store

Headquarter office

Workshop

Logistics

Home

and others

## Specification

NVR Specification	
Operating System	Embedded LINUX
Pentaplex	Simultaneous View, Record, Playback, Backup, and Remote Monitoring
Number of Channels	4
Inputs/Outputs	
Video IN	4 PoE Video Input
Video OUT	HDMI only ( without VGA)
Audio IN/Out	N/A
USB Port	2 at the back (one USB 3.0)
Alarm IN/Out	N/A
Video Output Resolution	MAX 4K
PTZ control	IP PTZ cameras with Onvif profile-S
Display	
Live Display	1, 2x2
Live Display Speed	120 NTSC, 100 PAL
OSD	ON/OFF
System Navigation	USB Mouse
Motion Area Setting	Adjustable grid (22x18)
Sensitivity levels	1-6
Firmware Upgrade	via USB device or network
User Authority	By user group
Time Synchronization	Auto time sync by NTP server
Recording	
Video Compression	H.265/H.264 selectable
Resolution	4MP (2592*1520), 3M(2048*1536), 1080P (1920x1080)
Record Rate	NTSC: 120FPS @ 4MP PAL: 100FPS @ 4MP
Record Resolution Setting	Per camera for different resolutions
Recording Quality	6 Levels
Record Schedule	By hour, by day, by recording mode, by motion, by channel
Reliability	Watch-Dog, auto-recovery after power failure
Covert Video	Yes
Playback	
Playback Channel	1/4
Playback Speed	Variable Max 8x
Search	By time & event

Storage & Archive	
Storage	Up to 1 HDD (SATA)
Maximum Capacity	Up to 1 x 6TB
Backup Media	USB flash drive, HDD, & Network
Backup File Format	H.264/H.265 or AVI file
Storage & Archive	
Cloud Connection	GOLBONG P2P Cloud
Supported OS	Windows™, Mac OS
Remote Software	GOLBONG Operation Software, CMS5
Email Notification	Text
Instant Smart Phone & Tablet Support	iPad®, iPhone®, Android™
System Configuration	Auto or manual
Network Protocol	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter
Network Interface	10/100–Base-TX, RJ-45
NVR General	
Power Consumption	10 watts (No HDD Installed)
Supply Voltage	100VAC-240VAC, 48V DC, 1.5A,
Total PoE Power Output	50W (across all channels)
Camera	
Imaging Device	4.0MP 1/3" CMOS
Effective Pixels	2592*1520
Day / Night	Auto (ICR) / Color / B/W
Min. Illumination	0.5lux (Color); 0.05lux (B/W)
S/N Ratio	>50dB
Field of View (H)	82°
Lens Type	3.6mm fixed lens, F1.6
IR Illumination	Yes, 850nm
Video Output	RJ45
Video	
Video Compression	H.265/H.264 selectable
Resolution	4MP (2592*1520), 3M(2048*1536), 1080P (1920x1080)
Aspect Ratio	16:09
Frame rates (Maximum)	4MP (2592*1520)@ 25fps
Bit Rate Selection	Compression Type: 56K~ 8129Kbps
Wide Dynamic Range	Digital WDR
Backlight Compensation	BLC / HLC / DWDR
Noise Reduction	3D
ONVIF Conformance	Profile S (v2.1)