

## 5804-34

# Network Keyboard



### Key Vaule Highlight

**- Control IP Network PTZ camera**

The network keyboard can control IP PTZ camera directly, manipulate pan/tilt/zoom with 3D joystick.

**- Built-in LCD display**

Built-in 8 inch LCD display provide the real time video during the operation.

**- Decode the video without PC platfrom**

The keyboard can work as decoder and output to 2 HDMI monitor with 16 channel maximum decoding each.

**- Complete open**

The decoder can work with 3rd-party ip camera basing on onvif protocols.

### Typical Application

Headquarter office

Hotel

City Surveillance

Telecom

Logistics Center

and others

## Specification

### Rated Voltage and Power

|                         |                             |
|-------------------------|-----------------------------|
| Rated Voltage and Power | 110–240 VAC; 50/60 Hz; 1.5A |
| External power adapter  | DC12V/2A                    |

### Video

|                |                      |
|----------------|----------------------|
| Video Standard | PAL or NTSC          |
| Compression    | H.264                |
| IP Decoding *  | 1080p, 720p, D1, CIF |
| Outputs        | HDMI                 |

### Monitors

|                 |   |
|-----------------|---|
| Display         | 8 inch LCD, 1200x600  |
| HDMI            | Live, menus   |
| Live Resolution | SVGA: 800x600, 1024x768, 1280x1024, 1360x768, 1440x900, 1920x1080 |

### Connections

|          |  |
|----------|--|
| Ethernet | 10/100/1000 Base-T, auto-sensing, half/full duplex, RJ45 |
| USB      | 2 USB 2.0  |
| HDMI     | 2 HDMI   |
| RS485    | 1 RS485  |

### Network

|                   |                                     |
|-------------------|-------------------------------------|
| Supported devices | Golbong IP Cameras, Onvif IP camera |
|-------------------|-------------------------------------|

### Mechanical

|  |                            |
|--|----------------------------|
| Dimensions (W x D x H) (excluding cabling) | 450(L) x 245(H) x 125(W)mm |
| Weight                                     | 3kg                        |

### Environmental

|                       |  |
|-----------------------|--|
| Operating temperature | +5 °C to +45 °C (+41 °F to +113 °F)                              |
| Storage temperature   | -25 °C to +70 °C (-13 °F to +158 °F)                             |
| Relative humidity     | Operating: <93 % non-condensing<br>Storage: <95 % non-condensing |

### Ordering Information

|                  |         |
|------------------|---------|
| Network Keyboard | 5804-34 |
|------------------|---------|

### Guangzhou

No.3 East Alley, Guangfeng East Road,  
Zengchen District, Guangzhou., 511300,  
P.R.China  
Tel: +86-20-8244-2660  
Fax: +86-20-8274-5925  
Email: sales@golbong.com

### Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,  
Baoan District, Shenzhen, 518000,  
P.R.China  
Tel: +86-755-81465995  
Fax: +86-755-81469770  
Email:sales@golbong.com