

5804-60

Network Storage Device



Key Vaule Highlight

- Auto Register Connecting

Golbong IP cameras, NVRs, and DVRs on multi-sites can register to this server without static IP address.

- Reliable Architecture

The 5804-60 can keep working 24/7 with its embedded linux system.

- Response to the IPC alarm

The 5804-60 can respone the alarm input from Golbong ip cameras and generate immediatly video pop up on the screen.

- Mass Storage.

The 5804-60 is capable of taking 16 unit hard disk with 96 TB space which can keep recording all channels more than 10 days in 1080p resolution.

- Monitor devices' status

The operator can read the status of each IP devices on multi-sites, receiving alarm message from motion detection, alarm I/O.

- Authorized Users

The operator can create unlimited accounts and assign the specific cameras for each users to access remotely.

- Complete open

The users can integrate 5804-60 with 3rd party ip camera which support Onvif protocols. The motion record can accomplish as long as the camera has followed the message notification instruction.

Typical Application

Headquarter office

Campuses

Hotel

City Surveillance

Telecom

Logistics Center

and others

Specification

Rated Voltage and Power

Rated Voltage and Power	110–240 VAC; 50/60 Hz; 1.5A
Redundant Power	N/A

Video

Video Standard	PAL or NTSC
Compression	H.264
Outputs	VGA (for configuration)

Alarm Handling

Inputs	IPC alarm
Events	Motion detect, Video Blind, Video Loss, IPC Alarm, Local Alarm
Remote notification	Via Control Center software

Connections

Ethernet	1 x 10/100/1000 Base-T, auto-sensing, half/full duplex, RJ45
USB	2 USB 3.0 ports, 6 USB 2.0 ports

Network

Protocols	RTSP, ONVIF, iSCSI, NFS, CIFS, FTP, HTTP, AFP
IP cameras	200 channel at 2Mbps
Video Forwarding	64 channel at 2mbps
Supported IP H.264 devices	Golbong Video Server, IP Cameras, Onvif 2.0 compliance IPC

Storage

Internal HDD	16 unit
Interface/Capacity:	SATA/1TB,2TB,3TB,4TB,6TB
Hot-swapping	supported
RAID	N/A

Security

Password protection	Multi-level
---------------------	-------------

Recording

Overwrite modes	Continuous, overwrite
-----------------	-----------------------

Mechanical

Dimensions (W x D x H) (excluding cabling)	440(L) x 133(H) x 671(W)
Weight	20 kg

Environmental

Operating temperature	+5 °C to +45 °C (+41 °F to +113 °F)
Storage temperature	-25 °C to +70 °C (-13 °F to +158 °F)
Relative humidity	Operating: <93 % non-condensing Storage: <95 % non-condensing

Ordering Information

Network Storage Device	5804-60
------------------------	---------

Guangzhou

No.3 East Alley, Guangfeng East Road,
Zengchen District, Guangzhou., 511300,
P.R.China
Tel: +86-20-8244-2660
Fax: +86-20-8274-5925
Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,
Baoan District, Shenzhen, 518000,
P.R.China
Tel: +86-755-81465995
Fax: +86-755-81469770
Email: sales@golbong.com