

MYEYE Platform Server



Key Vaule Highlight

- Auto Register Connect

The MYEYE server can connect Golbong IP cameras, NVRs, and DVRs on multi-sites without know each of its IP address.

- Manage IP devices

The operator can configure each IP camera, NVR, or DVR on the site from the monitoring center.

- Monitor devices' status

The operator can read the status of each IP devices on multi-sites, receiving alarm message from motion detection, alarm I/O.

- Video Re-generated

The MYEYE server can re-generate video and streams to the network for remote accessing.

- Search Right Video

The operator can find the right video recording on the cameras or recorders from the monitoring center.

- Create Umlimited Users

The operator can create unlimited accounts and assign the specific cameras for each users to access remotely.

- Mobile access

The users can access the re-generated feed from mobile phone anywhere.

Typical Application

Retail
Convenience Store
Headquarter office
Workshop
Logistics
Home
and others

Specification

General	
Maximum Number of Cameras	Unlimited (Please Refer to System Requirements Below)
Support OS	Windows 8, 7, Vista, XP Windows Server 2012, 2008, 2003, 2000
LiveView (Local Display)	
Max. Channel	64-Channel (With dual monitor)
Layout	Multi Layout display: 1x1, 2x2, 1+5, 1+7, 3x3, 1+12, 4x4, 5x5, 6*6, 8*8, Single Layout display, Full screen display, Sequential display
Stream Application	Stream Selection
Playback	
Max. Channel	9 Channel
Layout	Multi Layout display: 1x1, 2x2, 3x3, Single Layout display, Full screen display
Playback Mode	Server & On-board Storage
Playback Control	Play, Rewind, Pause, Stop, Next / Previous Video Start, Speed Control
Search Mode	Date & Time, Timeline Event, Alarm, Timeline
Video	
Video Format	H.264 AVC, H.265
Video Resolution	Up to 5 Megapixel
Video Enhancement	Brightness, Hue, Contrast, Saturation
Audio	
Audio Format	G.711
Audio Capability	Two Way
Audio Control	Mute & Sound Play
Record	
Recording Time (sec.)	Post-Record: 10-60
Recording Stream	Single
Recording Mode	Continuous (Schedule, Manual, Event) *
Recording Setting	Recycle
Recording File Format	H.264 or H.265

Alarm Management	
Alarm Setting	LiveView Alarm Notification, Alarm Count
eMap	
Source	Import Picture *
Marked	Add, Remove, Indicator LiveView *
PTZ	
PTZ Control	Panel Control
PTZ Operation	Direction Control, Zoom, Focus, Iris, Preset, Tour, Speed
Export	
Snapshot	BMP
Export file	AVI
System	
User Management	Authentication: Basic Account
Date & Time	Sync PC
Language	Czech, English, French, German, Italian, Japanese, Persian, Portuguese, Russian, Spanish, Simplified Chinese
Camera Integration	
Camera Insert	Manual, Search, Auto discovery
Basic Setting	Date & Time, video standard, DST
Connection Setting	TCP/IP, DAS, Cloud, Email, FTP, DDNS, PPPoE, RTSP
Video Setting	Video Stream, Compression, Resolution, FPS, Video Quality
Audio Setting	On/Off
Event	Motion detection, Abnormal
Local Storage	Utilities, recording schedule

Guangzhou

No.3 East Alley, Guangfeng East Road,
Zengchen District, Guangzhou., 511300,
P.R.China
Tel: +86-20-8244-2660
Fax: +86-20-8274-5925
Email: sales@golbong.com

Shenzhen

1/F Block 295, Jiuwei, Xixiang Town,
Baoan District, Shenzhen, 518000,
P.R.China
Tel: +86-755-81465995
Fax: +86-755-81469770
Email: sales@golbong.com